



Variable speed control dial

allows operator to adjust cutting speed depending on material or application.



Dual LED job lights



Dust and drip-proof performance is enhanced for use in outdoor applications or harsh environments.

Accessories


Dust Extractor Attachment Set

Part No. 199142-6

Dust Extractor Attachment Set  
Hammering only

without Vacuum hose set  
Part No. 199143-4

with Vacuum hose set  
Part No. 199144-2



Li-ion Battery & Charging Time Reference, Compatibility Chart

	BL1815N 18V 1.5Ah	BL1820B 18V 2.0Ah with Battery fuel gauge	BL1830B 18V 3.0Ah with Battery fuel gauge	BL1840B 18V 4.0Ah with Battery fuel gauge	BL1850B 18V 5.0Ah with Battery fuel gauge	BL1860B 18V 6.0Ah with Battery fuel gauge
Two Port Multi Fast Charger 	15 min	24 min	22 min	36 min	45 min	55 min



Cordless Rotary Hammer	DHR400 40 mm (1-9/16")
Variable Speed	<b>Impact Energy</b> EPTA-Procedure 05/2009: 8.0 J Our experimental conditions: 11.4 J
Brake	<b>Capacity</b> Concrete (w/ T.C.T. bit) : 40 mm (1-9/16") Concrete (w/ Core bit) : 105 mm (4-1/8")
Reversing	<b>Blows Per Minute (BPM)</b> 1,450 - 2,900
SDS-MAX Shank	<b>No Load Speed (RPM)</b> 250 - 500
Torque Limiter	<b>Sound Pressure Level</b> 91 dB(A)
Constant Speed	<b>Sound Power Level</b> 102 dB(A)
Soft Start	<b>Vibration Level</b> Hammer Drilling Into Concrete: 5.0 m/s <sup>2</sup>
Dust Collection	<b>Dimensions</b> 473x120x285 mm
Built-in Job Light	<b>(L x W x H)</b> (18-5/8"x4-3/4"x11-1/4")
Carrying Case	<b>Net weight</b> 7.3 - 8.1 kg (16.1 - 17.9 lbs)
	<b>Standard Equipment :</b> Side Handle, Side Grip, Depth Gauge, Bit Grease, Cloth, Wireless Unit (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge.  
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.  
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201801

Satisfy Professional's Needs



Cordless Rotary Hammer  
DHR400 40 mm (1-9/16")



Adapted for  
SDS-MAX bits

High Power  
similar to  
AC Tool



Extra Comfort with unrivaled low level of vibration

AVT & SOFT  
ANTI VIBRATION TECHNOLOGY NO LOAD







Adapted for  
SDS-MAX bits

# Excellent performance equivalent to AC Model



Newly developed BL motor  
delivers high power



## Drilling work amount

Work volume on a single full battery charge

About **25** holes

- ◆ w/ T.C.T. bit Ø18mm
- ◆ Depth : 140mm
- ◆ Concrete : 40 N / mm<sup>2</sup>
- ◆ Battery : BL1850B x2

## Demolition work

with bull point

## Impact Energy

[ EPTA-Procedure 05/2009 ]

**8.0J**

Makita HR4013C 8.0J



# AVT & SOFT NO LOAD

ANTI VIBRATION TECHNOLOGY

Vibration absorbing  
housing isolates handle  
and motor.

Active dynamic vibration  
absorber moves in the  
opposite direction to the  
drive piston to reduce  
vibration.

Damper spring absorbs  
impact vibrations from  
the drill bit.



**AWS**

Auto-start Wireless System



Wireless unit

Part No.  
198901-5,  
198900-7(EU)

**Bluetooth**

Switch on the tool  
Vacuum cleaner is activated

■ Comparison of Vibration level\* and Time to reach ELV  
(Exposure Limit of Vibration)\*\*

\* It is known as the tri-axial value and value at  
Directive of A(8).

\*\*It means the maximum amount of vibration that an  
operator may be exposed to on any single day.

Time to reach ELV (min)	100	200	550	
Makita DHR400	5.0m/s <sup>2</sup>		540min	
Makita HR4013C	5.0m/s <sup>2</sup>		540min	
Vibration level (m/s <sup>2</sup> )	0	5	10	15

**AWS connects to power tool  
via Bluetooth.**

Wireless unit



**Bluetooth**

The Bluetooth® word mark and logos are registered trademarks owned  
by the Bluetooth SIG, Inc. and any use of such marks by Makita is under  
license. Other trademarks and trade names are those of their respective  
owners.

**Expand AWS Line-up**

**AWS**

